



# Precision Geosynthetic Laboratories

Corporate Office & Main Laboratory : 1160 North Gilbert Street, Anaheim, CA, 92801, Tel.: (800) 522-4599



SEND YOUR SEAMS TO:

## PGL MAIN LABORATORY

ATTN: CHRISTIAN SEBASTIAN  
1160 North Gilbert Street  
Anaheim, California, 92801  
Tel. No.: (800) 522-4599

DATE : \_\_\_\_\_

PROJECT NAME / PROJECT NUMBER: \_\_\_\_\_

PROJECT LOCATION: \_\_\_\_\_

New  Repair

| Seam ID |           |           |          |                  | Type of Welding Process |           |              | Type of Material |       |            | TEST METHOD<br>(Check which is applicable)   |
|---------|-----------|-----------|----------|------------------|-------------------------|-----------|--------------|------------------|-------|------------|--|
| Item    | DS Number | Panel No. | Location | Name of Operator | FUSION                  | EXTRUSION | Solvent Weld | HDPE             | LLDPE | rPP/PVC/PP |  |
| 1       |           |           |          |                  |                         |           |              |                  |       |            | SHEAR - ASTM D4437 <input type="checkbox"/><br>PEEL - ASTM D4437   |
| 2       |           |           |          |                  |                         |           |              |                  |       |            | SHEAR - ASTM D751 <input type="checkbox"/><br>PEEL - ASTM D413<br>Crosshead Speed = 2"/min   |
| 3       |           |           |          |                  |                         |           |              |                  |       |            | SHEAR - ASTM D4437 (NSF Modified) <input type="checkbox"/><br>Crosshead Speed= 20"/min<br>PEEL - ASTM D4437 NSF Modified<br>Crosshead Speed= 20"/min |
| 4       |           |           |          |                  |                         |           |              |                  |       |            |  |
| 5       |           |           |          |                  |                         |           |              |                  |       |            | SHEAR - ASTM D3083 <input type="checkbox"/><br>Crosshead Speed= 20"/min<br>PEEL - ASTM D413 Crosshead Speed= 2"/min                                  |
| 6       |           |           |          |                  |                         |           |              |                  |       |            |  |
| 7       |           |           |          |                  |                         |           |              |                  |       |            |  |
| 8       |           |           |          |                  |                         |           |              |                  |       |            | HDPE <input type="checkbox"/><br>SHEAR - ASTM D6392<br>PEEL - ASTM D6392   |
| 9       |           |           |          |                  |                         |           |              |                  |       |            |  |
| 10      |           |           |          |                  |                         |           |              |                  |       |            | LLDPE / PVC <input type="checkbox"/><br>SHEAR - ASTM D6392<br>PEEL - ASTM D6392  |
| 11      |           |           |          |                  |                         |           |              |                  |       |            |  |
| 12      |           |           |          |                  |                         |           |              |                  |       |            | SHEAR - ASTM D4437 (NSF Modified) <input type="checkbox"/><br>Crosshead Speed = 2"/min   |
| 13      |           |           |          |                  |                         |           |              |                  |       |            |  |
| 14      |           |           |          |                  |                         |           |              |                  |       |            | PEEL - ASTM D4437 (NSF Modified)<br>Crosshead Speed = 2"/min   |
| 15      |           |           |          |                  |                         |           |              |                  |       |            |  |

|                      |       |                                |       |
|----------------------|-------|--------------------------------|-------|
| <b>REPORT TO</b>     |       | <b>RELEASED BY</b>             |       |
| NAME :               | _____ | NAME :                         | _____ |
| COMPANY :            | _____ | COMPANY :                      | _____ |
| ADDRESS :            | _____ | DATE/TIME :                    | _____ |
| TEL NO. :            | _____ | <b>RECEIVED BY</b>             |       |
| FAX NO. :            | _____ | Precision Geosynthetic Labs    |       |
| E-MAIL :             | _____ | NAME :                         | _____ |
| <b>FIELD CONTACT</b> |       | <b>SHIPPED VIA</b>             |       |
| NAME :               | _____ | O Fedex            O DHL       |       |
| TEL NO. :            | _____ | O UPS                O US Mail |       |
| Mobile No. :         | _____ | O Hand Carry      O Others     |       |
| FAX NO. :            | _____ | Tracking Number: _____         |       |
| E-MAIL :             | _____ |                                |       |

**NOTES:**  
PGL Laboratories are normally OPEN on SATURDAYS for SEAM TESTING.  
To ensure that your package is delivered/received on Saturdays; please fax, e-mail or call to let us know the AIRBILL # of your package. This will help us track down samples for SATURDAY DELIVERY.

**PLEASE WRITE YOUR INSTRUCTIONS BELOW**

Thickness required?  Yes  NO

**IF SOLVENT WELD:**  
Curing Time: \_\_\_\_\_? Curing Temp: \_\_\_\_\_?